

DATA SHEET: LED CANOPY (60-120W) Square type

Features

- Sealed die-casting prole for indoor and outdoor applications.
- Voltage is 120-277V & 347-480V.
- Lumen: 120-140lm/W. (optional)
- Provide with a PIR sensor ideal for parking garage and optional for emergency battery.
- Replacing 100W MH-250W MH.
- Operating temperature is -40°C to 40°C (-40°F to 104°F).
- ETL wet location listed and DLC qualified.
- Limited Warranty 5 year (10 year optional)
- IP65
- RA>0.7



Applications:

Parking structures, storage areas, shopping aea walkways, entryway, and low level security.

Line-Up


Model No	Watts(W)	Light Output(lm)	Dimension(mm)	Light Color(K)	Beam Angle(Degree)	Power Factor(PF)
CR-CPHD60	60W	7800LM	265*265*90	3000K-6500K OPTIONAL	150°	> 0.9
CR-CPHD80	80W	10400LM	265*265*90	3000K-6500K OPTIONAL	150°	> 0.9
CR-CPHD100	100W	13000LM	265*265*90	3000K-6500K OPTIONAL	150°	> 0.9
CR-CPHD120	120W	15600LM	265*265*90	3000K-6500K OPTIONAL	150°	> 0.9

Environmental Requirements

Specifications	Values
Operational Temperature Range	-40~40°C
Preservation Temperature Range	-40~90°C
Operational Humidity Range	95%Rh or below (@-40~40°C)
Installation Area	Indoor (Counter,Residential,Commercial,etc)

DISTRIBUTION

Parking Garage



CrownDA·LED

GUANGDONG CROWNDA TECHNOLOGY CO., LTD

Dimension

